

Data Sheet / Wayne Helix™ 6000 II AdBlue® dispenser

Reducing Engine Emissions

Fuel Compatibility

- AdBlue®
- Diesel Exhaust Fluid (DEF)

Model Availability

- Orientation: Lane. Dual-sided or Single-Sided
- Grades available: 1
- Nozzles available: 1 to 4. Also available as a back-2-back model for up to 5 grades in total
- Hydraulic System: Remote Pressure
- Hose Management: Full Hose Retraction (FHR)
- Flow Rates available: 10 or 20 lpm

Hose Reach

- FHR: 4.0 meter reach

Electronics

- iGem pump computer

Displays

- Premium 7-6-5 LED with 1.15" digits

Totalizers

- Electromechanical 7-digit totalizers

Communication Protocol

- DART as standard. Other protocols available

Metering

- Secure intelligent pulser
- Electronic calibration
- Piston meter technology using P-Meter

Heating

- Optional heating system available
- ATEX heating

Branding

- Optional customized graphics

Materials

- Painted hot dipped galvanized steel frame
- Painted hot dipped galvanized steel cladding

Corrosion Protection

- C4 protection according to ISO12944-2:1998 as standard

Relative Humidity

- From 5% to 95%

Operating temperature

- From -25°C to +55°C as standard
- Optional low temperature kit option for extended temperature range -40°C to +60°C

IP Rating

- IP 54 electronic head

Certifications

- ATEX
- OIML
- MID



DFS Worldwide Brands