

The new DD 1500 has a modular structure so you can choose the configuration that suits you best. All components are selected to suit the Nordic winter climate and to last for many years. Of course, our pumps meet all statutory requirements.



Configurations

The DD 1500 is supplied as a single or double pump, with a capacity of 40, 80 or 130 liters per minute. Choose the configuration that best suits your needs.

- Single pump
- Double pump

- 40 litres/minut
- 80 litres/minut
- 130 litres/minut

The fuels

The DD 1500 is designed for pumping and metering various diesel products, including HVO, RME and other bioproducts.

Quality and approvals

DD 1500 meets all requirements for CE marking. The pump is robust and built to last for many years even under demanding conditions. All components are selected to withstand the Nordic winter climate.

Integrated or separate terminal

The DD 1500 can be equipped with an integrated terminal and modem for data communication, which suits smaller facilities without a separate card terminal, or supplied for connection to an existing/ separate terminal.

- Integrated terminal
 - » Direct connection to TapNet
 - » Can be connected to AdBlue pump at the same time
 - » Can be connected to the washer fluid pump at the same time
 - » Refueling with card, tag or with CODAB's own app (for iOS or Android).
- Separate terminal, for example PT 1000 or PT 4000

Service and installation

We have a nationwide network for installation, technical support and service. All our dispensers can be debugged remotely. Often, problems can also be solved without a technician needing to be sent out. If it still proves necessary to visit the facility, the remote diagnostics will inform you of which spare parts are needed.